

WCA	Description Weber-Calibra	DIN	EN	Taux PB max%
Laiton sans plomb				
201	CuZn28	2.0261	CW-504L	0.05 %
202	CuZn33	2.0280	CW-506L	0.05 %
203	CuZn36		CW-507L	0.05 %
204	CuZn37	2.0321	CW-508L	0.10 %
205	CuZn23Al3Co		CW-703R	0.05 %
207	CuZn42-PNA378		CW-510L	0.03 %
208	CuZn42-PNA380		CW-510L	0.03 %
Alliage TOMBAC				
710	CuZn5	2.0220	CW-500L	0.05 %
720	CuZn15	2.0240	CW-502L	0.05 %
Maillechort sans plomb				
301	Cu64Ni25Zn11 - ARCAP® AP1			0.03 %
302	Cu56Ni25Zn19 - ARCAP® AP1C			0.03 %
303	CuNi12Zn24	2.0730	CW-403J	0.03 %
304	CuNi18Zn20	2.0740	CW-409J	0.03 %
Bronze phosphoreux				
520	CuSn6	2.1020	CW-452K	0.02 %
560	CuSn8	2.1020	CW-453K	0.02 %
Alliage d'aluminium				
910	Al99.5	3.0255	AW-1050	Pas pb
925	AlMg3	3.3535	AW-5754	Pas pb
Fers				
*RFe 80	Fer 04	1.1014		Pas pb

*Stock minimum, nécessite réapprovisionnement si nous recevons une commande conséquente

